



See Reverse Side of Page
for Skirt Sizes and
Installation Instructions

Pole-Safe® Skirt
3003-H14 Aluminum Sheet,
1.6 mm (1/16") Thick
(4 panels per Skirt)

Bolt Circle Diameter

Pole-Safe® Couplings
(Typical, 4 per Pole)

Pole Base Plate

Skirt Height
(H)

#10 x 10 mm (#10 x 3/8")
Stainless Steel Sheet Metal
Screw, Typical, 8 per Skirt

Pole-Safe® Skirt Details
Breakaway Support System for Light Poles



20 Jones Street
New Rochelle, NY 10801
914-636-1000
www.transpo.com

Melted and Manufactured in the USA

01/14



Pole-Safe®
Breakaway Support System for Light Poles

SKIRT INFORMATION

Selection Table:

Pole-Safe® Model No.	Bolt Circle Diameter		Skirt Height (H) mm (in.)
	254 mm to 380 mm (10" to 15")	380 mm to 500 mm (15" to 20")	
	Skirt Part No.	Skirt Part No.	
4062	SPMKDN-4	SPMKDN-4L	146 (5-3/4)
4075	SPMKDN-4	SPMKDN-4L	146 (5-3/4)
4100	SPMKDN-5	SPMKDN-5L	168 (6-5/8)
4125	SPMKDN-5	SPMKDN-5L	168 (6-5/8)
5062	SPMKDN-1	SPMKDN-1L	108 (4-1/4)
5075	SPMKDN-1	SPMKDN-1L	108 (4-1/4)
5100	SPMKDN-2	SPMKDN-2L	127 (5)
5125	SPMKDN-3	SPMKDN-3L	133 (5-1/4)

Installation Instructions:

1. Place 4 skirt panels around Pole-Safe Couplings using overlap configuration shown on reverse side of page. All 4 sides of the skirt box should have 2 slots facing outside.
2. Thread 8 sheet metal screws through the outside slots into the closest corresponding holes in the adjacent inside panel.
3. Position panels snug against the Pole-Safe Couplings.
4. Tighten all 8 sheet metal screws.

Transpo Industries, Inc., 20 Jones Street, New Rochelle, NY 10801-6098
Phone: 914-636-1000 Fax: 914-636-1282
www.transpo.com